

Operating Instructions P4720 Night Colors™

Congratulations on your purchase of the Night Colors™ LED Night Light. Please read these operating instructions thoroughly before use. It is important for proper use of the product.

With Night Colors™, you can experience a soothing multi-colored light show in any room of your house. This ingenious night light is equipped with LED lights that gently change color—from red to pink, violet to blue, teal to green. Have a favorite color? Simply choose the freeze mode and Night Colors™ will remain in the chosen hue.

WARNING

! Designed for indoor use only. Do not use outdoors. !

! The unit is not waterproof. Do not place the unit where it will become immersed in water. !

! The unit is not water resistant. Do not place in a damp or very humid area. !

! Do not use if your hands are wet. !

! If the unit becomes cracked, broken, deformed or in any other way damaged, discontinue use immediately. Discard or return for service. !

Installation:

- Insert unit into standard 110 VAC household outlet.
- When power is first applied, the unit will **not** respond to presses. After a few seconds, mode selection becomes active. This is to eliminate unintentional mode changes when installing the unit.
- Unit is designed to be oriented with the flat edge downward. This provides a white down light effect for lighting hallways and stairways.
- If desired, it can be installed with the flat edge upward - washing the wall with white light.
- Do not install the unit where it can be hit by swinging doors, windows, or other household objects.
- Do not install the unit in a floor-mounted outlet.
- Do not install the unit at the end of an extension cord or in any other location where it can be stepped on.

Use:

- Unit features eight operation modes.
- When initially powered, unit will start in mode 1.
- Press momentarily on the face of the unit to select the next mode.
- Pressing the face in mode 8 will return to mode 1.

When power is first applied, the unit will **not** respond to presses. After a few seconds, mode selection becomes active. This is to eliminate unintentional mode changes when installing the unit.

Mode	Description
1	Normal cycle: Colors will cycle through all combinations repeating every approx. 30 seconds. White down light on.
2	Freeze mode: Lock in your favorite color choice from the normal cycle. White down light on.
3	Off: All LEDs extinguished.
4	White down light only: Only the white LED is lit, illuminating your hallway, stairway, or washing the wall with light.
5	Slow cycle: Colors will cycle through all combinations repeating every approx. 120 seconds. White down light on.
6	Red: Pure red light. White down light on.
7	Green: Pure green light. White down light on.
8	Blue: Pure blue light. White down light on.

TIP: Pressing the face of the unit will always change the mode. It might not change the color. For example, Mode 2 will freeze the current color from the normal cycle.

TIP: The light output of the unit is designed for night light applications. For best results use in a darkened room.

TIP: The normal cycle mode is automatically engaged when power is applied. This is the most engaging and active mode.

TIP: If you get “lost,” cycles through the modes until the LEDs are off (Mode 3). Then refer to the above mode chart.

P3 INTERNATIONAL CORPORATION LIMITED WARRANTY

P3 INTERNATIONAL CORPORATION (“P3”) warrants to the original retail purchaser only, that its product is free from defects in material or workmanship under the condition of normal use and service for a period of six (6) months from the date of purchase. In the event that a defect, malfunction or failure occurs or is discovered during the warranty period, P3 will repair or replace at its option the product or component part(s) which shall appear in the reasonable judgment of P3 to be defective or not to factory specifications. A product requiring service is to be returned to P3 along with the sales receipt or other proof of purchase acceptable to P3 and a statement describing the defect or malfunction. All transportation costs shall be borne by the owner and the risk of loss shall be upon the party initiating the transportation. All items repaired or replaced thereunder shall be subjected to the same limited warranty for a period of six (6) months from the day P3 ships the repaired or replaced product. The warranty does not apply to any product that has been subject to misuse, tampering, neglect, or accident or as a result of unauthorized alterations or repairs to the product. This warranty is void if the serial number (if any) has been removed, altered, or defaced. This warranty is in lieu of all warranties expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose which are expressly excluded or disclaimed. P3 shall not be responsible for consequential, incidental or other damages, and P3 expressly excludes and disclaims liability for any damages resulting from the use, operation, improper application, malfunction or defeat of any P3 product covered by this limited warranty. P3’s obligation is strictly and exclusively limited to the replacement or repair of any defective product or component part(s). Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. P3 does not assume or authorize anyone to assume for it any other obligation whatsoever. Some states do not allow limitation on how long an implied warranty lasts, so the above limitations may not apply to you. It is the owner/user’s responsibility to comply with local, state, or federal regulations, if any, that may pertain to P3 products or their use. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

If you experience difficulty in the operation of your product, or if your product requires service please contact:

P3 INTERNATIONAL CORPORATION
 TECHNICAL SUPPORT
Email: techsupport@p3international.com
 Tel: 212-741-7289
 Fax: 212-741-2288

rev. 04/04