

Operating Instructions P7400 Glowstone™

Congratulations on your purchase of Glowstone™. Please read these operating instructions thoroughly before use. It is important for proper use of the product.

The Glowstone™ motion sensitive garden light can make your garden or yard glow with life. The unit will detect when somebody passes by and illuminate for up to 30 seconds. Its realistic granite finish complements your garden or yard.

WARNING

! Ensure the unit is closed securely before placement. !

! Do not place the unit where it will become immersed in water. Be careful not to place unit where incoming tide may flood it. !

! Do not place under edge of roof where rain run-off may flood the unit. Do not place in low-lying ground where rain collects. !

! Do not leave unit outdoors in extreme weather conditions. Extreme winds, heat, or cold could damage the unit. !

! Do not operate unit without rubber seals on battery-box in place. Moisture may enter the circuit and cause damage. !

! We recommend the use of alkaline batteries. Rechargeable and other types will not provide equivalent performance. !

Installation:

- Unit requires 4 X C alkaline batteries (not included). Use fresh batteries. Do not mix brands or age of batteries.
- Remove battery-box by turning Glowstone™ upside down and rotating base/battery-box counter-clockwise. **Gently** remove base/battery-box from stone body. **Do not strain** cable connection.
- If necessary, disconnect cable from battery-box by pulling straight up on cable. **Batteries can be installed without disconnecting the cable (recommended).**
- Open battery-box cover by unhooking long tab. Use a screwdriver to “pop” tab to avoid injury. Do not damage tab by applying too much pressure.
- Insert 4 fresh C batteries observing polarity diagram in base of battery-box.
- Re-attach battery-box cover insuring a tight seal.
- If desired, change bulb illumination timer by removing rubber cap and moving switch with a small screwdriver. Set to 5, 15, or 30 seconds. Unit comes pre-set at 15 seconds. Re-attach rubber cap ensuring a tight seal.
- Ensure bulb is tight and bulb seal is in place.
- If disconnected, reconnect cable. Note connector is “keyed” to only fit one way. Ensure seal for cable connection is firmly pressed against the battery-box.

- Replace base/battery-box by fitting pins into holes in the stone body. Rotate clockwise until snug. Note base is shaped to match stone body. If the shape does not match after the base is replaced, it is backwards. Remove, rotate 1/2 turn and re-attach.
- Place Glowstone™ on dry ground. Do not place in dips or ruts where rainwater might collect.
- Aim PIR motion sensor (white “eye” shaped dome) at the target area.

Use:

- **Unit will not illuminate in daylight. An internal light sensor will activate the unit at dusk and deactivate at dawn.**
- Unit will detect passers by at a range of up to 12 feet and illuminate momentarily. This range will vary according to surroundings.
- Experiment with placement and aim of PIR motion sensor to achieve desired results.
- Bulb illumination timer will affect battery life. We recommend leaving it set at 15 seconds. For longer illumination set to 30 seconds. For very short illumination set to 5 seconds.
- If you note a dimming of the lamp, or no illumination, replace batteries. Discard exhausted batteries properly.

P3 INTERNATIONAL CORPORATION LIMITED WARRANTY

P3 INTERNATIONAL CORPORATION (“P3”) warrants to the original retail purchaser only, that its product is free from defects in material or workmanship under the condition of normal use and service for a period of six (6) months from the date of purchase. In the event that a defect, malfunction or failure occurs or is discovered during the warranty period, P3 will repair or replace at its option the product or component part(s) which shall appear in the reasonable judgment of P3 to be defective or not to factory specifications. A product requiring service is to be returned to P3 along with the sales receipt or other proof of purchase acceptable to P3 and a statement describing the defect or malfunction. All transportation costs shall be borne by the owner and the risk of loss shall be upon the party initiating the transportation. All items repaired or replaced thereunder shall be subjected to the same limited warranty for a period of six (6) months from the day P3 ships the repaired or replaced product. The warranty does not apply to any product that has been subject to misuse, tampering, neglect, or accident or as a result of unauthorized alterations or repairs to the product. This warranty is void if the serial number (if any) has been removed, altered, or defaced. This warranty is in lieu of all warranties expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose which are expressly excluded or disclaimed. P3 shall not be responsible for consequential, incidental or other damages, and P3 expressly excludes and disclaims liability for any damages resulting from the use, operation, improper application, malfunction or defeat of any P3 product covered by this limited warranty. P3’s obligation is strictly and exclusively limited to the replacement or repair of any defective product or component part(s). Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. P3 does not assume or authorize anyone to assume for it any other obligation whatsoever. Some states do not allow limitation on how long an implied warranty lasts, so the above limitations may not apply to you. It is the owner/user’s responsibility to comply with local, state, or federal regulations, if any, that may pertain to P3 products or their use. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

If you experience difficulty in the operation of your product, or if your product requires service please contact:

P3 INTERNATIONAL CORPORATION
TECHNICAL SUPPORT
71 West 23rd Street
Suite 1201
New York, NY 10010-4102

Tel: 212-741-7289
Fax: 212-741-2288

Email: techsupport@p3international.com

rev. 04/02